



## KONICA Auto SE

An Electronic shutter equipped fully automatic camera. 6 transistors, 3 diodes and 2 magnets are used for the shutter assembly. By the length of time for charging the condenser, which changes according to the brightness of subjects, the automatic mechanism between lens openings and shutter speeds is controlled. Accurate and steady exposure control can be done. Film advance and shutter setting are automatically performed by spring motor.

### Specifications

|                   |                                                                                                                                                                                                                                                                                |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Picture Size:     | 24 x 36 mm                                                                                                                                                                                                                                                                     |
| Film:             | 35 mm film in the safety cartridge                                                                                                                                                                                                                                             |
| Lens:             | HEXANON 38 mm f/1.8; 6 elements in 4 groups                                                                                                                                                                                                                                    |
| Shutter:          | SEIKOSHA ELECTRONIC SHUTTER, programmed system; EV 5.7 (f/1.8 1/15 sec) to EV 17 (f/16 1/500); X contact (1/30 sec); with selftimer; flash matic system                                                                                                                        |
| Viewfinder:       | Bright frame; x 0.59 magnification; parallax and picture angle automatic compensation; red warning mark in the finder when out of automatic mechanism                                                                                                                          |
| Range-finder:     | Double image system; effective triangulation base 24.8 mm; minimum range 0.6 meter (2 ft)                                                                                                                                                                                      |
| Exposure Control: | Super sensitive CdS light metering system; fully automatic mechanism (EE); Photocell provided upper front of the lens barrel; reflected light type; subject coverage 10 degrees up and down, 14 degrees left and right; a mercury battery 1.3 V used; battery checker provided |
| Film Advance:     | 20 pictures can be taken consecutively at one full charge of the spring motor; the spring is to be released by pushing the film rewind button or by opening the camera back-lid                                                                                                |
| Film Counter:     | Automatic resetting to Start Mark when the back-lid is opened; three frames of from Start Mark to No. 1 are to be advanced automatically by winding the spring motor                                                                                                           |
| Film Rewind:      | Film rewind is to be made by Crank after pushing the button; the button is reset when the back-lid is opened or by operating the wing nut for the spring motor                                                                                                                 |
| Synchro-socket:   | Cordless contact; another synchro-socket provided to the side of finder cover                                                                                                                                                                                                  |
| Filter:           | Screw-in type; screw dia. 49 mm, pitch, 0,75 mm                                                                                                                                                                                                                                |
| Hood:             | Slip-on type                                                                                                                                                                                                                                                                   |
| Dimensions:       | 134.8 x 78.8 x 60 mm 770 grs.                                                                                                                                                                                                                                                  |



## KONICA Auto SE

An Electronic shutter equipped fully automatic camera. 6 transistors, 3 diodes and 2 magnets are used for the shutter assembly. By the length of time for charging the condenser, which changes according to the brightness of subjects, the automatic mechanism between lens openings and shutter speeds is controlled. Accurate and steady exposure control can be done. Film advance and shutter setting are automatically performed by spring motor.

### Specifications

|                   |                                                                                                                                                                                                                                                                                |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Picture Size:     | 24 x 36 mm                                                                                                                                                                                                                                                                     |
| Film:             | 35 mm film in the safety cartridge                                                                                                                                                                                                                                             |
| Lens:             | HEXANON 38 mm f/1.8; 6 elements in 4 groups                                                                                                                                                                                                                                    |
| Shutter:          | SEIKOSHA ELECTRONIC SHUTTER, programmed system; EV 5.7 (f/1.8 1/15 sec) to EV 17 (f/16 1/500); X contact (1/30 sec); with selftimer; flash matic system                                                                                                                        |
| Viewfinder:       | Bright frame; x 0.59 magnification; parallax and picture angle automatic compensation; red warning mark in the finder when out of automatic mechanism                                                                                                                          |
| Range-finder:     | Double image system; effective triangulation base 24.8 mm; minimum range 0.6 meter (2 ft)                                                                                                                                                                                      |
| Exposure Control: | Super sensitive CdS light metering system; fully automatic mechanism (EE); Photocell provided upper front of the lens barrel; reflected light type; subject coverage 10 degrees up and down, 14 degrees left and right; a mercury battery 1.3 V used; battery checker provided |
| Film Advance:     | 20 pictures can be taken consecutively at one full charge of the spring motor; the spring is to be released by pushing the film rewind button or by opening the camera back-lid                                                                                                |
| Film Counter:     | Automatic resetting to Start Mark when the back-lid is opened; three frames of from Start Mark to No. 1 are to be advanced automatically by winding the spring motor                                                                                                           |
| Film Rewind:      | Film rewind is to be made by Crank after pushing the button; the button is reset when the back-lid is opened or by operating the wing nut for the spring motor                                                                                                                 |
| Synchro-socket:   | Cordless contact; another synchro-socket provided to the side of finder cover                                                                                                                                                                                                  |
| Filter:           | Screw-in type; screw dia. 49 mm, pitch, 0,75 mm                                                                                                                                                                                                                                |
| Hood:             | Slip-on type                                                                                                                                                                                                                                                                   |
| Dimensions:       | 134.8 x 78.8 x 60 mm 770 grs.                                                                                                                                                                                                                                                  |



## KONICA EE-Matic 260

Fully automatic camera with instant loading system created by the latest camera manufacturing technique.

Flash Cube Socket built in and Focusing can be done by Range-finder.

### Specifications

|                          |                                                                                                                                                                                       |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Picture Size:</b>     | 28 x 28 mm                                                                                                                                                                            |
| <b>Film:</b>             | Kodapak 126 Type in the safety cartridge                                                                                                                                              |
| <b>Lens:</b>             | HEXANON 42 mm f/2.8; 4 elements in 3 groups                                                                                                                                           |
| <b>Shutter:</b>          | SEIKO LA programmed automatic shutter, 1/30 — 1/250 sec; flash synch 1/30 sec; switchover to Flash by manual operation of setting ASA speed                                           |
| <b>Finder:</b>           | Bright frame; double image system; x 0.6 magnification; effective triangulation base 15.6 mm; closest distance, 0.9 meter (3 ft); "Use Flash" signal appears                          |
| <b>Exposure Control:</b> | Automatic control by automatic mechanism (EE)                                                                                                                                         |
| <b>EE Control Range:</b> | ASA automatic change; 64, 80, 125, 160; EV 8 (f/2.8 1/30 sec — EV 17 (f/22 1/250 sec); "Use Flash" signal appears in the finder when out of automatic mechanism; release button locks |
| <b>Film Advance:</b>     | Single stroke wind-up by cocking lever; multiple exposure prevention; operation angle 130 degrees                                                                                     |
| <b>Flash:</b>            | Flash Cube used exclusively; battery, 2 pcs.; flash cube rotation coupled to film advance;                                                                                            |
| <b>Dimensions:</b>       | 79.6 x 130.3 x 34.3 mm                                                                                                                                                                |

# KONICA Super 8 6-TL

Most advanced 8 mm cine camera of TTL light metering system, with x 6 Zooming Ratio. Accurate and steady exposure control can be done by servo-mechanism. Manual aperture setting and closing down of lens-opening possible.



## Specifications

|                                       |                                                                                                                                                                                                   |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Film:</b>                          | Super 8 film                                                                                                                                                                                      |
| <b>Lens:</b>                          | V-HEXANON 8—48 mm f/1.8 (Zooming Ratio x 6); 13 elements in 10 groups; focusing distance, 1 meter to infinity                                                                                     |
| <b>Zooming:</b>                       | Motor driven auto zoom. Manual operation possible                                                                                                                                                 |
| <b>Finder:</b>                        | Single lens reflex type; cross prism built in; with over/under exposure warning mark; aperture value indication; back-light preventing shutter built in                                           |
| <b>Exposure Control:</b>              | Automatic system by servo-mechanism; TTL light metering system; ASA coupled range 16—400, automatic setting; aperture coupled range 1.8—22, manual setting, closing down of lens-opening possible |
| <b>Main Motor &amp; Power Source:</b> | Three speed micromotor; 1.5 V x 4 (penlight batteries)                                                                                                                                            |
| <b>Filming Speed:</b>                 | 12, 18, 24 frames per second and also single frame                                                                                                                                                |
| <b>Film Counter:</b>                  | Automatic resetting type; ratchet device for every one foot feed; scale indication up to 50 ft. (Metric scale indicated on the same unit)                                                         |
| <b>Filter:</b>                        | Type 85 built in; filter setting is coupled to the type of film and also to bar-light                                                                                                             |
| <b>Grip:</b>                          | Fixed to camera. Batteries and battery checker are contained in the Grip                                                                                                                          |
| <b>Remote Control:</b>                | Provided                                                                                                                                                                                          |
| <b>Shutter Button:</b>                | Trigger type fitted to the upper part of the Grip                                                                                                                                                 |
| <b>Bar-light:</b>                     | Designed to be fitted on to the upper part of the camera                                                                                                                                          |

# KONICA Super 8 3-TL

A sister 8 mm cine camera of KONICA SUPER 8 6-TL. Fully automatic mechanism is actuated by TTL system used CdS. ASA-speed is automatically set when the super 8 cartridge is loaded.

## Specifications

|                          |                                                                                                                                                                  |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Film:</b>             | Super 8 film                                                                                                                                                     |
| <b>Lens:</b>             | V-HEXANON 9.5—28.5 mm f/1.8                                                                                                                                      |
| <b>Zooming:</b>          | Manual zooming                                                                                                                                                   |
| <b>Finder:</b>           | Single lens reflex type; over-exposure indication mark; eyesight adjustment                                                                                      |
| <b>Exposure Control:</b> | TTL system by CdS meter; fully automatic mechanism (EE); ASA coupled range 16—100, automatic setting; shutter-release locking device for under-exposure built in |
| <b>Driving:</b>          | Electric motor; 1.5 V x 4 (penlight batteries)                                                                                                                   |
| <b>Film Drive:</b>       | 18 frames per second                                                                                                                                             |
| <b>Film Counter:</b>     | Automatic resetting type                                                                                                                                         |
| <b>Filter:</b>           | Type 85 built in; filter setting is coupled to the type of film and also to bar-light                                                                            |
| <b>Grip:</b>             | Detachable                                                                                                                                                       |
| <b>Remote Control:</b>   | Possible                                                                                                                                                         |



# KONICA

## Super 8 2Z

Easy-to-handle Super 8 Cartridge System. Operation of Zoom V-HEXANON 10-20 mm f/1.8 is by lever. Fully automatic mechanism (EE) is actuated by CdS. Film speed is automatically set when the super 8 cartridge is loaded.

### Specifications

|                   |                                                                                                                                                    |
|-------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Film:             | Super 8 film                                                                                                                                       |
| Lens:             | V-HEXANON 10-20 mm f/1.8                                                                                                                           |
| Zooming:          | Manual zooming                                                                                                                                     |
| Finder:           | Separate type; over-exposure warning mark                                                                                                          |
| Exposure Control: | CdS meter; fully automatic mechanism (EE); ASA coupled range 16-100, automatic setting; shutter-release locking device for under-exposure built in |
| Driving:          | Electric motor; 1.5 V x 4 (penlight batteries)                                                                                                     |
| Film Drive:       | 18 frames per second                                                                                                                               |
| Film Counter:     | Automatic resetting type                                                                                                                           |
| Filter:           | Type 85 built in; filter setting is coupled to the type of film and also to bar-light                                                              |
| Grip:             | Detachable                                                                                                                                         |

# KONICA Super 8 S

A sister 8 mm cine camera of KONICA SUPER 8 2 Z. Fully automatic mechanism is actuated by CdS. Film speed is automatically set when the super 8 cartridge is loaded.

### Specifications

|                   |                                                                                                                                               |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Film:             | Super 8 film                                                                                                                                  |
| Lens:             | HEXANON 12.5 mm f/1.8                                                                                                                         |
| Finder:           | Separate type; over-exposure warning mark                                                                                                     |
| Exposure Control: | CdS meter; fully automatic mechanism; ASA coupled range 16-100, automatic setting; shutter-release locking device for under-exposure built in |
| Driving:          | Electric motor; 1.5 V x 4 (penlight batteries)                                                                                                |
| Film Drive:       | 18 frames per second                                                                                                                          |
| Film Counter:     | Automatic resetting type                                                                                                                      |
| Filter:           | Type 85 built in; filter setting is coupled to the type of film and also to bar-light                                                         |
| Grip:             | Detachable                                                                                                                                    |