

ERASE, RECORD AND RECORD/PLAYBACK HEADS

<u>STEREO R/PB</u>	L	Z	Bias at	AF Current	O/P/kHz	DC
		at 1 kHz	100 kHz		at 7½ ips	Resistance
					32 mil/mm	

UK.202B *Record*  
 2/2 track 120 mH 780 ohms 24V .70mA 110 micro A 2. mV 50 ohms

UK.200B *Playback*  
 2/2 track 550 mH 3.5K ohms 60V .50mA 50 micro A 5. mV 300 ohms

UK.205B  
 2/4 track 550 mH 3.5K ohms 60V .45mA 40 micro A 3. mV 630 ohms

UK.207B  
 2/4 track 120 mH 780 ohms 25V .5mA 70 micro A 1.8 mV 170 ohms

MONO R/PB

UK.100B 550 mH 3.5K ohms 65V .40mA 50 micro A 6. mV 200 ohms

All R/PB heads have 3 micron gaps.

MONO RECORDING HEAD

UA.127B  
 10 Micron Gap 350 mH 1.8K 60V .30mA 60 micro A 120 ohms

ERASE HEADS

L

Current and Voltage @ 100 Kc/s

UL.197 (½ track) 5 mH 30 mA 120 V 15 ohms

UL.290 (2/2 track stereo) 2 mH 45 mA 70 V 5 ohms

UL.296 (2/4 track stereo) 2 mH 40 mA 65 V 9 ohms