

EPICURE

Model 400 Plus The Minitower

"The stereo properties of omni speakers
are at least comparable to those of a
live performance . . ."

(Julian Hirsch, Stereo Review)

Epicure's goal is to provide state-of-the-art reproduction of sound. Our ability to manufacture the Tower, the ultimate among all loudspeakers, demonstrates our advanced technology. Based on this vast experience, Epicure offers the Model 400 Plus, our ultimate multiple module loudspeaker.

The Model 400 Plus, a direct descendant of the unsurpassed Tower, is a true omnidirectional loudspeaker. It utilizes Epicure's unique air spring efficiency-matched tweeter and woofer concept thus eliminating all crossover devices. Without these devices, the full range of transients inherent in all music are unveiled and allowed to cascade throughout the room. In addition, the low mass principle is employed in the design of both the tweeter and woofer. This allows the Minitower's air spring tweeter to respond instantaneously to all musical variations and permits the woofer to accurately track extremely low frequency signals.

These exceptional innovations, combined with unsurpassed realism obtainable only with omnidirectional loudspeakers, create the most transparent and clear musical sounds you have ever heard. And, the Minitower's appearance reflects the consistent high quality of all Epicure's products. The finest hardwood veneers and solid, hand-rubbed walnut houses the Minitower in a distinctive cabinet that enhances any decor.

The Minitower, from Epicure.

Model 400 Plus The Minitower

The spherical sound of the Model 400 Plus totally envelopes you with dynamic sound. It is as clear and vibrant as the original performance. At all power levels, the Minitower reproduces the true essence of musical sounds without the unnatural coloration or distortion present in many other loudspeakers. Since the Minitowers are omnidirectional speakers, the sound image remains distinct regardless of room placement, provided a direct line of sight exists between you and your Minitower.

SPECIFICATIONS:

Size:	14 x 14 x 38 inches
Weight:	90 lbs.
Frequency Response:	27 Hz to 19,000 Hz ± 3 dB
Recommended RMS Power Range:	25 to 200 Watts RMS
Dispersion:	Omnidirectional, nearly hemispherical radiation from each radiating plane
Crossover Frequency:	1800 Hz; each set of transducers are custom matched within 1 dB of efficiency, thus eliminating all electronic crossover devices present in most other types of loudspeakers
Drivers:	4 - 1" Air spring transducers 4 - 6" Low frequency transducers
Tweeter Level Control:	Three-position toggle switch
Inputs:	General Radio type connectors

*© beim Hersteller
Archiv Michael-Otto*



EPICURE
A STEP CLOSER TO REALITY

One Charles Street, Newburyport, Massachusetts 01950