

NEWS FROM

garrard

Vertriebs GmbH

Sonderangebot 1/82



Modell B 20

Riemenantriebener Plattenspieler

mit automatischer Tonarmrückführung **Motor:** AC-Synchron, 4-polig.
Gleichlaufschwankung: 0,1% **Rumpel-Geräuschspannungsabstand:**
65dB (DIN B), **Plattenteller:** 307 mm \varnothing , 0,9 kg Gewicht, Druckgußalumi-
nium, **Tonarm:** 230 mm, gerade Ausführung, 10 gm Gewicht, Drehpunkt
gelagert (konisch + Kugellager) viskosegedämpft. Mitgeliefertes Ton-
abnehmersystem: EXCEL ES 70S oder Ortofon FF 15
Abmessungen: 450(B)x126(H)x380(T)mm (geschlossen)
450(B)x385(H)x399(T)mm (bei geöffneter Haube)

DM 

+ MwSt.

zahlbar **sofort netto**
frachtfreie Anlieferung
Gültig bis: 19.02.1982

Weitere Auskünfte erhalten Sie von

 **garrard**
Vertriebs GmbH

Spessartstraße 2
D-8752 Stockstadt/Main
Telefon (0 60 27) 25 25 / 26 26
Telex 04 188 587 garh d



Mitglied im DHI

Garrard D-20

Auto Return Direct Drive Turntable with Strobe and Pitch Control.

© beim Hersteller
Archiv Michael Orto
HiFi-Classic.de



 **garrard**

Garrard D-20

Technical Specification.

OPERATION MODE

Auto Return

STONE ARM

Type	Straight.
Effective Length	230 mm. (9")
Effective Mass (Less cart.)	10 gm.
Pivots	Cone and Ballrace.
Tracking Force	0.75 gm. recommended minimum.
Tracking Force Adjustment	Isolated counterbalance weight, calibrated, one gramme per revolution, 0.1 gm. divisions.
Cartridge Weight	4.5 to 9 gm.
Bias Compensator for Cue Control	0-3 gm. Tracking Force Viscous damped, up and down.

DRIVE

Motor	Coreless DC direct drive with velocity servo control. FG feedback.
Speeds	33 $\frac{1}{3}$ and 45 rpm.
Pitch Adjustment	$\pm 5\%$
Starting time (33 $\frac{1}{3}$ rpm)	2 Sec. ($\frac{1}{2}$ platter rev.)
Stroboscope	Stroboscope synchron- ised to mains frequency.

PLATTER

Diameter	307 mm. (12")
Type	Die cast aluminium with stroboscope.
Weight (with mat)	1.3 Kgm.
Mat	Rubber, recessed to support playing area of record.

CONTROLS

Slider controls for: 33 $\frac{1}{3}$ and 45 rpm speeds, Stop/
Start, Cue control. Auto return button. Bias
compensator knob. Edge wheel pitch control.

PERFORMANCE

Rumble (DIN A)	- 50 dB.
Rumble (DIN B)	- 70 dB.
Wow (DIN slow weighted)	0.05%

DIMENSIONS

With cover (WxHxD)	450 x 126 x 380 mm. (ins.)
With cover open	450 x 385 x 395 (17.7 x 15.2 x 15.5)

Garrard's policy is one of continuous improvement and development, we therefore
reserve the right to change specifications without prior notice.

Garrard Vertriebs GMBH,
Spessartstrasse 2,
D-8751 Stockstadt/Main.
Telefon (0 60 27) 25 25/26 26.
Telex 04 188587. Reply code ARH D.

 **garrard**

Garrard Limited,
Cheney Manor Industrial Estate, Swindon SN2 2QQ.
Telephone (0793) 35381. Telex: 44271.