



The GL 72 P


Here is ample proof that high-quality Hi-Fi equipment does not have to be expensive if it is designed with the skill and care that Goldring bring to every item in their range.

The Goldring-Lenco GL 72 P is not an expensive turntable. Simply a very good one.

It incorporates continuously-variable speeds, in this case from 30 r.p.m. to 86 r.p.m., with pre-set click-in stops at $16\frac{2}{3}$, $33\frac{1}{3}$, 45 and 78 r.p.m.

It is fitted with the lightweight L.69 arm which is lowered gently on to the record by a viscously-damped lowering device.

The bias compensation is simple yet effective, giving you scope to use high-quality stereo cartridges.



Shown here is the Goldring 800 stereo magnetic cartridge, a unit which skilfully combines the sometimes conflicting requirements of high fidelity and robust design.

The unit is mounted on the very attractive teak base together with dust cover shown. Also in chassis form.

Dimensions (with plinth):

Closed: $17\frac{1}{2}$ in. x $13\frac{3}{4}$ in. x 6 in.
 Open: $17\frac{1}{2}$ in. x $16\frac{1}{2}$ in. x $16\frac{1}{2}$ in.
 (Chassis): 15 in. x 12 in. x $4\frac{3}{4}$ in.



The GL 75 P


The Goldring-Lenco GL 75 P is already widely acclaimed as a superbly-integrated transcription unit that looks as good as it sounds. Now we've achieved the impossible by improving it a little more.

By adding a luxurious new plinth of hand-finished teak. And a new de-luxe dust cover with satin chrome trim. To make quite sure that the good looks of the GL 75 continue to live up to its performance.

When you look into the works you will find still more to attract you. The drive is the unique Goldring-Lenco constant velocity 4-pole motor. The 9-lb turntable die-cast from non-ferrous material is dynamically balanced. Speed is continuously-variable from 86-30 and 18-15 r.p.m. – invaluable for those who wish to vary the tempo of their records.

There is only a 0.2% change of speed for 10% mains voltage change.

Shown here is an ideal running mate for the GL75 P – the Goldring 800/E stereo magnetic cartridge – with its micro-elliptical diamond.



The unit is also available in chassis form.

Dimensions (with plinth):

Closed: 17½ in. x 13¾ in. x 6 in.

Open: 17½ in. x 16½ in. x 16½ in.

(Chassis): 15 in. x 13 in. x 5⅝ in.