



harman/kardon

hk750 high technology integrated amplifier

The new hk750 is the logical extension of our widely acclaimed 700 Series High Technology Separates—a sophisticated, integrated amplifier that produces 45 watts per channel into 8 ohms.

As with the rest of the 700 Series, the 750 has been designed with low negative feedback to keep TIM and THD well below audible levels.

The 750 also has features you might not expect on other comparable integrated amps. Like a 5 stage, fully discrete phono pre-amp section that's extremely fast and quiet. Plus a toroidal power supply that can easily handle two pairs of speakers while substantially reducing both hum and stray noise. Two tape copy/monitor positions are provided for dubbing and monitoring. And the 750 also features loudness control, subsonic and hi cut filters, as well as tone defeat.

The hk750 integrated amplifier is the perfect solution for the audiophile who wants the sophistication of our High Technology Separates with the simplicity and economy of an integrated amplifier.

Preliminary Specifications: hk750

AMPLIFIER SECTION	
RMS Power into 8 ohms (20-20,000 Hz):	45 watts @ less than 0.03% THD
Frequency response at rated output:	below 1 Hz–150 kHz (–3 dB)
IM/TIM distortion at rated output:	0.05%/0.01%
Slew rate/power amplifier:	60 volts/ μ sec.
Overall negative feedback:	25 dB
Hum & noise "A" WTD	
Phono/Aux/Residual:	–88 dB/–100 dB/–100 dB
Phono overload:	>150 mV