

T-1 LUXMAN AM/FM STEREO TUNER

PACKAGE '80

SPECIFICATIONS

FM SECTION (IEEE/F Standard)	(MONO) (STEREO)
Usable Sensitivity	(60dB) (3.5V)
50dB Quieting Sensitivity	(60dB) (0.5V)
Signal-to-Noise Ratio at 55dB	75dB (HF A-weighted)
Frequency Response	10Hz-20kHz 15dB
Distortion at 65dB	100Hz 0.15% 0.15%
	1kHz 0.15% 0.15%
	6kHz 0.15% 0.15%
Capture Ratio at 55dB	1.4dB
Adjacent Channel Selectivity	60dB
Alternate Channel Selectivity (-400kHz)	75dB
Spurious Response Ratio	80dB
IF Response Ratio	90dB
Image Response Ratio	75dB
AM Suppression Ratio	75dB
Stereo Separation	100Hz 8dB
	9kHz 14dB (AES with 100Hz filter)
	10kHz 20dB

Subcarrier Product Ratio	0dB
SCA Rejection Ratio	60dB
Muting Threshold	1V
Output Level	700mV
AM SECTION	
Usable Sensitivity at 1MHz, 400Hz 30% mod	22mV/m
Image Response Ratio at 1MHz	75dB
IF Response Ratio at 1MHz	80dB
Signal-to-Noise Ratio at 1MHz, 10mW/m	
	400Hz 30% mod: 55dB
Distortion at 1MHz, 10mW/m, 400Hz 30% mod	0.5%
[GENERAL]	
Power Consumption	1W
Dimensions	438(W) x 212(H) x 86(D) mm
	(17 1/4" x 12 3/32" x 3 1/2")
	(37")
Weight	Net 3.6kg (11.9 lbs)
	Gross 6.0kg (13.2 lbs)



The Package '80 Series audio components offer the best cost-performance, providing fresh and elegant utility to your listening space.

The exclusively designed rack LK-1 accommodates the L-1, T-1 and K-1 perfectly in the modern style.

*© Herm Fiersteller
Archiv Michael Otto*

L-1 SPECIFICATIONS

POWER OUTPUT: 15W + 15W (100V)
T.D.R. (Distortion): 0.05% (100V)
(100V) (100V) (100V)
more: 100V (100V) (100V)
FREQUENCY RESPONSE: 10Hz-20kHz (+1.5dB)
S/N RATIO: better than 95dB (Spectrum, HF-A, 10mV) 100dB (Spectrum, HF-A)
RESIDUAL NOISE: 0.5mV, CROSSTALK: 10dB (max), ADDITIONAL FEATURES: Tape Monitor, Tape Ejecting, Loudness Control, Mode Selector, Speaker Terminals (A & B), Phono Schottky Filter, Low Cut Filter, DIMENSIONS (DRW) = 306(D) x 86(H) mm, WEIGHT: 7.0kg (15.4 lbs)

K-1 SPECIFICATIONS

HEAD: Emerald, WOW & FLUTTER: 0.05% (W.B.M.S.), S/N RATIO: 94dB (METAL, Delay OFF) 60dB (METAL, Delay ON) FREQUENCY RESPONSE: 10Hz-20kHz (METAL) OVERALL DISTORTION: 1.5% (0.1% typical) INPUT SENSITIVITY: 10mV (100V) 8.2mV (100V) OUTPUT LEVEL: 500mV (100V) ADDITIONAL FEATURES: Rec. Mute, 3-position Bias/EQ Selector, SKEW Adjust Hole, VU Meter, Delay NR System, Headphone Jack, DIMENSIONS: 438(W) x 206(D) x 100(H) mm, WEIGHT: 3.2kg (11.4 lbs)

AUTHORIZED DEALER



LUX AUDIO OF AMERICA, LTD.
100 DUPONT ST. PLAINVIEW, NEW YORK 11803 U.S.A.

LUX CORPORATION, JAPAN.

1-1, 1-CHOME, SHINSEIJI-NISHIMACHI,
TOYONAKA-SHI, OSAKA, JAPAN.
PHONE: 06-834-2222 CABLE: LUXMAN TOYONAKA TELEX: J03094

LUXMAN

T-1

LUXMAN AM/FM STEREO TUNER

*High sensitivity and selectivity
through the creative circuit assure your listening enjoyment.
The exclusive Flasket Tuning System
ensures precise station selection.*



*© beim Hersteller
Archiv Michael Otto*



**PACKAGE
'80**

The Luxman photo gallery

LUX CORPORATION, JAPAN

01 April 2003

<http://luxman.fotopic.net>