



Fig. 2. McIntosh C24 Solid-State Stereo Preamp.

The C 24 Solid-State Stereo Preamp

This unit is being included with the MR 71 tuner profile because a preamp is generally used in conjunction with a tuner, because it is very similar in appearance, and because its performance is similarly superb.

The McIntosh C 24 employs a total of 18 silicon planar transistors—eight in each of the two channels (which are identical), one in the "center-channel" (L+R) output, and one as a voltage regulator in the power supply section. The phono/tape head preamp employs three transistors, with RIAA or LP equalization selected for phono by a slide switch, followed in turn by the mode-selector switch, loudness control, channel balance, the first section of the volume control, and an emitter-follower which drives a Baxandall-type tone-control circuit. This is followed by two more amplifier stages, the rumble and noise filters, and the output amplifier using two transistors. The second section of the volume control is next, followed by a voltage divider/mixer network feeding the L+R amplifier stage. Two silicon diodes serve as the power rectifier, and the voltage is regulated to 75 volts by the 18th transistor, and further regulated to 10 volts by a zener diode. A four-second time-delay circuit is provided to ensure that the full voltage is not applied to the circuit abruptly, thus allowing the various capacitors to charge up without the usual annoying "thump" which is generally heard when a non-delayed transistor amplifier is first turned on.

So far, nothing particularly new or startling has been said about the C 24, which is as it should be. What is unusual about the over-all philosophy of the C 24 is the channeling of the power amplifier output through the preamp chassis before going to the loudspeakers.

This feature is to permit switching of the speakers, as well as to provide a panel-mounted jack for headphones, and to permit reversing the phase of one speaker from the control position, rather than in back of the speaker itself, which is often enough of a chore as to preclude its being done, even when it might improve the listening. (Not all sources—tape, records, or broadcasts—are always perfect in this regard). In less careful design, this proximity of high-level outputs might cause trouble, but in this unit the shielding effectively precludes any trouble from this arrangement.

With the speaker switch, headphone jack, and phase-control switch at the control center of this system, the user has almost every possible flexibility that he might need—or want. This feature has been encountered before in receivers, but so far we have not seen it in a preamplifier/control unit.

Performance

There is little need to state that the C 24 is flat within 0.5 db from 20 to 20,000 cps or that the equalization curves follow the prescribed values within ± 2 db throughout the audio spectrum—we have learned to expect that from any good preamp over the past few years—but the distortion figures are somewhat remarkable. The output is rated at 2.5 volts, and at this value the distortion is less than 0.1 per cent from 20 to 20,000 cps. Even at a 10-volt output the distortion measures less than 0.3 per cent over the same range. What is especially important is the amount of phono (or tape head) input this unit will handle without clipping. We have learned by now that this is one figure that should be measured first in any test of transistor amplifiers.

Before describing the phono performance of the C 24 in this respect, let us examine the possible amplitude of the signal from a modern pickup cartridge. We have actually measured stylus amplitudes of more than 40 cm/sec on some phonograph records—not many, we'll admit, but on some. The usual output from a stereo cartridge is in the vicinity of 1.0 to 1.5 mv per cm/sec of

stylus velocity—some as much as twice that. We have been told by some record companies that their *peak* recording level was 5 cm/sec, (which we do not believe), and by others that the *average* level was 5 cm/sec. Assuming it is average, and with an estimated increase of peak over storage of 10 db, this would mean a peak level of 16 cm/sec. A clearance of 16 db is usually considered safer as the margin between average and peak program levels, which would imply that peak velocities of 30–35 cm/sec could be reached easily. At an output from the cartridge, of, let us say, 1.1 mv per cm/sec, this would mean that the signal applied to the input of the preamp could reach 33–38 mv. Now if the preamp should clip at an input of 30 mv (we are speaking only of a 1000-cps signal) distortion would certainly result. With the high-frequency boost in modern recording techniques, more efficient microphones in the high-frequency region, and the inclination of A and R men to feature trumpets and strings, overload of the preamp can cause breakup which is extremely unpleasant.

None of this is likely to occur with the C 24 because under the worst combination of volume and loudness control settings, the preamp will not clip (at 1000 cps) until the input signal reaches 100 mv. Under most conditions of settings, the clipping level is 135 mv. Equalization takes care of the high frequencies, and rolloff of the bass in the recording process takes care of the low frequencies. We feel this is a most important problem, and it seems to have been solved in the C 24 quite satisfactorily. At least, we have not ever heard any evidences of clipping on phono. We can not see much application of the 10-volt output capability of the C 24, but if it can supply this much signal with less than 0.3 per cent distortion, it should be able to coast along nicely at the usual 0.25 to 1.0 volts required for normal room levels.

From its Ivory tower, McIntosh modestly claims 99.9 per cent perfection—we'll give 'em only $99\frac{44}{100}$ per cent. We would make only one minor change—that of reversing the direction of rotation of the contour control. At present, clockwise rotation increases the amount of equalization, but decreases level. We would prefer it the other way. In the maximum position, there is a boost of approximately 10 db at 30 and 10,000 cps with respect to 1000 cps, which follows general contouring practice.

Tone controls give a range of ± 18 db at 20 and 20,000 cps. Lo-cut starts at about 100 cps and is down 11.5 db at 30 cps, 32 db at 10 cps. Hi-cut starts at 3000 cps and is down 7 db at 10,000 cps, 16 db at 20,000. In the flat position of all controls, over-all response is down

only 6 db at 100,000 cps, if that should matter to anyone.

On high-level inputs, noise and hum measured 78 db below rated output with the volume control at maximum. In the minimum position of the volume control, the noise drops to 112 db below rated output—as it should, of course, since one section of the volume control immediately precedes the output jacks. On the phono input, noise measures 64 db below rated output at the maximum setting of the volume control. At a volume control setting which gives an output of 1 volt at a phono input of 10 mv, the noise and hum were down 72 db.

With these impressive performance figures, the C 24 is truly a fitting companion for the "superb" MR 71 stereo tuner.

Circle 220