

McIntosh C26



C 26 SHOWN IN OPTIONAL WALNUT VENEER CABINET

Solid State Preamplifier

Performance is important to your listening expectations. With a McIntosh you are assured of highest performance because McIntosh guarantees performance. Your C 26 must be capable at meeting its advertised performance limits or your purchase price will be refunded. McIntosh promises performance and delivers performance.

Low distortion is a requirement for high performance in a preamplifier. A typical wave form analysis of the C 26 at 2.5 volts output is a 99.95% perfect reproduction of the input wave, 20 Hz through 20,000 Hz!

RELIABILITY

Endless hours are invested by our engineers carefully and thoroughly testing and retesting individual component parts. These hours are required to provide you with the highest degree of reliability that modern design and manufacturing can produce. As an example: The front panel is constructed of materials that are nearly indestructible. The combination of anodized aluminum and glass are impervious to attacks by acids and oils. The subtle beauty of the C 26 will remain unblemished year, after year, after year. This attention to detail increases the value of a McIntosh at trade in time. And because of the testing program, McIntosh promises you complete freedom from service costs for the first THREE YEARS that you own your C 26.

- Control remote loudspeaker and main system loudspeakers from the preamplifier
- Record on one or two tape recorders, monitor either one or record from one tape recorder to another!
- Headphone jack for low impedance **headphones**
- Stepped tone controls, separate in each channel permits the accurate repeatability of tone control settings
- Continuously variable loudness control permits amount of loudness compensation you want
- High frequency and low frequency filters
- Six-position input selector
- Center channel level control
- Phase control
- Balance control

The McIntosh C 26 is the best value in a solid state preamplifier, anywhere. You get complete protection from all service cost for three full years. Only McIntosh offers a free **THREE YEAR SERVICE CONTRACT**. You can't pay us to service your C 26 for the first three years you own it. Both parts and labor are included in the service contract. You are assured of highest performance because every unit is individually tested using internationally recognized test procedures. You are assured of greatest reliability because every component part is carefully tested and evaluated before it is designed in a McIntosh. The McIntosh C26 in the finest expression of **PERFORMANCE • RELIABILITY - FLEXIBILITY • BEAUTY.**

Performance Limits

Performance Limits are the maximum deviation from perfection permitted for a McIntosh Instrument. We promise you that the C26 you buy must be capable of performance at or exceeding these limits or you get your money back. McIntosh is the only manufacturer that makes this guarantee.

FREQUENCY RESPONSE: +0-0.5 dB 20 Hz to 20,000 Hz.

DISTORTION: Will not exceed 0.1% at rated output level, 20 Hz to 20,000 Hz.

INPUT SENSITIVITY AND IMPEDANCE:

AUXILIARY, TUNER, TAPE 1, TAPE 2 0.25 volts at 250,000 ohms.

PHONO 1 and PHONO 2 2 millivolts at 47,000 ohms (1,000 Hz),

HUM AND NOISE:

AUXILIARY, TUNER, TAPE 1, TAPE 2 85 dB below rated output.

PHONO 1, PHONO 2 74 dB below 10 millivolts input, equivalent to less than 2 microvolts at the input terminals.

OUTPUT LEVEL AND IMPEDANCE:

MAIN OUTPUT 2.5 volts with rated input, 200 ohms source impedance, to operate into 47,000 ohms or greater.

TAPE OUTPUT 0.25 volts from low level inputs, 200 ohms source impedance, to operate into 47,000 ohms or greater,

CENTER CHANNEL OUTPUT (L - R) 2.5 volts with rated input to both channels. 1,200 ohms source impedance to operate into 47,000 ohms or greater. A level control adjusts the CENTER CHANNEL output from -6 dB to -6 dB with respect to MAIN output

VOLTAGE AMPLIFICATION:

AUXILIARY, TUNER, TAPE 1 and TAPE 2 to MAIN OUTPUT 20 dB

To TAPE OUTPUT 0 dB

PHONO 1 and PHONO 2 (at 1,000 Hz) to MAIN OUTPUT 62 dB
to TAPE OUTPUT 42 dB

AC POWER OUTLETS:

1 unswitched (Red)
4 switched

POWER REQUIREMENT:

120 volts. 50/60 Hz, 15 watts

FACILITIES AND FEATURES

BASS

11 position rotary switch for each channel,

TREBLE:

11 position rotary switches for each channel.

LOUDNESS:

Flat response, or continuously variable

VOLUME:

Precision "tracked" at all listening levels. The AC power ON/OFF switch is coupled with this control.

LF FILTER (Rumble Filter)

Flat or roll-off 6 dB per octave below 50 Hz, down to 12 dB at 20 Hz.

HF FILTER (Scratch Filter)

Flat or roll-off 6 dB per octave above 6,000 Hz, down 12 dB at 20,000 Hz.

SPEAKER

MAIN — Switch MAIN loudspeaker system.

REMOTE — Switch REMOTE loudspeaker system.

TAPE MONITOR:

Two pushbutton switches. Either of two tape recorders can be monitored.

TRANSISTOR COMPLEMENT:

18 silicon-planar transistors and 3 silicon diodes.

MECHANICAL INFORMATION

SIZE: Front panel: 16 inches wide (40.64 cm) by 5-7/16 inches high (13.81 cm). Chassis: 15 inches wide (38.1 cm) by 5 inches high (12.7 cm) by 13 inches deep (33.02 cm) including PANLOC mounting brackets and back panel connectors. Knob clearance required is 1½ inches (3.81 cm) in front of the mounting panel.

FINISH: Front panel is anodized gold and black with special McIntosh gold/teal panel nomenclature illumination. Chassis is black.

MOUNTING: Exclusive McIntosh developed professional PAN-LOC.

WEIGHT: 18 pounds (8.16 kg) net, 33 pounds (14.97 kg) in shipping carton.

FRANCHISED DEALER

McIntosh LABORATORY INC.

2 Chambers St., Binghamton, N.Y. 13903

Phone area 607 723-3512