

ROTEL®

RA-211

STEREO PRE-MAIN AMPLIFIER



HERE is RA-211, a fully packed amplifier at modest cost. With power capability of 10W+10W RMS continuous power both channels driven at wide frequency response and negligible distortion, this amplifier can outperform other amplifiers of similar costs.

Besides all necessary controls, RA-211 also has connections for two pair of speakers you can use individually or simultaneously, a convenient loudness switch, and tape monitor facility. And ROTEL's tradition of excellent quality built into this small but superb machine.

ROTEL®

RA-211

SPECIAL FEATURES

- * Ample power for true high fidelity sound
- * All solid state electronics design
- * All silicon output transistors
- * Handsomely trimmed aluminum extrusion panel
- * Simple and easy-to-operate layout of controls
- * Rotary – Bass, Treble, Balance, Volume and Function Selector
- * Pushbuttons – Power, Speaker System 1, Speaker System 2, Loudness and Tape Monitor
- * Convenient headphone jack and power beacon
- * Facilities for magnetic and ceramic phonos, tuner, tape recorder and auxiliary component
- * Wood cabinet included

SPECIFICATIONS

Total Music Power (IHF)	50W at 4ohms	Signal to Noise Ratio:	
Continous Power (RMS)	16W+16W each channel driven at 4ohms	Phono	63 db
	12W+12W each channel driven at 8ohms	Aux	70 db
	13W+13W both channels driven at 4ohms	Tuner, Tape In	70 db
	10W+10W both channels driven at 8ohms	Residual Noise	1.5 mV
	(all less than 1% THD at 1kHz)	Damping Factor	35 at 8 ohms
Harmonic Distortion	0.2% at 9W+9W RMS, 8 ohms	Loudness Control	+8db at 50Hz, +3db at 10KHz
IM Distortion	0.6% at 9W+9W RMS, 8ohms	Bass Control	±10db at 50Hz
Frequency Response	20 to 65,000 Hz, -3db at 8 ohms	Treble Control	±10db at 10KHz
Power Bandwidth (IHF)	20 to 35,000 Hz at 8 ohms	Phono Overload	80 mV
Input Sensitivity/Impedance:		Phono Equalizer	RIAA
PHONO MAG	2.7mV/45K ohms	Crosstalk	-45db
PHONO 2 CERAMIC	140mV/100K ohms	Dimensions	13"(W)x6½"(D)x4"(H)
TUNER	170mV/50K ohms	Weight:	9 lbs/4 kg
AUX	170mV/50K ohms		
TAPE MONITOR IN	150mV/50K ohms		
TAPE DIN	330mV/100K ohms		



Note: Features and specifications subject to change without notice.