




TOSHIBA STEREO TAPE DECK

SERVICE DATA

MODEL PT-862

FILE NO. 100-058



SPECIFICATIONS

Usable Tape:	3", 5", 7"	Signal/Nois Ratio:	56 db minimum
Tape Speed:	7-1/2", 3-3/4" and 1-7/8ips(3 speeds)	Wow/Flutter:	0.09% R.M.S. maximum at 7-1/2ips
Track:	4 track(2 channels)		0.12% R.M.S. maximum at 3-3/4ips
Recording System:	AC bias at 105 KHz		0.18% R.M.S. maximum at 1-7/8ips
Erasing System:	AC erase	Power Consumption:	55 watts maximum
Frequency Response:	20 to 25000 Hz at 7-1/2ips 30 to 15000 Hz at 3-3/4ips 30 to 9000 Hz at 1-7/8ips	Transistor and Diode:	14 transistors, 12 diodes
Power Output:	LINE OUT 0 to 1 volt	Head:	3 heads
Input Jack:	MIC. 65db LINE IN. 23db	Dimensions:	(W) 15-9/16" (H) 14" (D) 7-13/32"
Output Jack:	LINE OUT HEADPHONE	Weight:	26.5 lbs
Power Source:	AC 100/110/120/200/220/240 volts, 50/60Hz		

TOKYO SHIBAURA ELECTRIC CO., LTD.

2-1, 5-CHOME, GINZA, TOKYO, JAPAN