

STEREO TAPE DECK PT-862

- 3-head system permits either tape or source monitoring and echo recording
- Mechanical automatic shut off and easy tape loading mechanism
- Tape selector switch and recording bias control
- Sound on sound system
- 4-digit tape counter
- Playback volume



© beim Hersteller
Archiv Michael Otto
HiFi-Geschichte

STEREO TAPE DECK PT-862

SPECIFICATIONS

GENERAL

Power source:	AC 100/110/120/200/220/240 V, 50 or 60 Hz
Usable tape:	Open reel tape, up to 7"
Tape speed:	19(7½), 9.5(3¾), 4.8(1⅞) cm/sec. (ips)
Track & channel:	4-track, 2-channel stereo record & playback
Bias & erasure:	AC, 85 kHz
Input jack:	Microphone, Line-input, DIN
Output jack:	Line-output, Headphone, DIN
Motor:	4-pole condenser motor
Controls:	Tape selector switch, speed change, power switch, volume control, mode selector
Operations:	Rotary (PLAY, STOP, F.F., REW.), PAUSE
Auxiliary device:	4-digit tape counter, easy loading mechanism, recording bias control
Dimensions:	390(W) × 355(H) × 186(D) mm (15⅝" × 12¼" × 7⅜")
Weight:	12 kg (26⅞ lbs.)
Accessory:	Patch cord, owner's manual, 7" blank reel, head cleaning stick, AC cord



PERFORMANCE

Output level & impedance:	0–1V (Variable), 500Ω (DIN; 0.5 V 6.8 kΩ)
Frequency response:	50–20,000 Hz
Tape speed tolerance:	±1%
Wow & flutter:	0.09% w.r.m.s.
Cross talk:	60 dB
Channel separation:	55 dB
Signal-to-Noise ratio:	56 dB
Erasure:	65 dB
Input level & impedance:	MIC; –65 dB 10 kΩ, Line-in; –23 dB 820 kΩ
FF time:	180 sec. (7" 100% tape)
Rewind time:	180 sec. (7" 100% tape)