

# 4 CHANNEL STEREO TAPE DECK PT-866

- 3-head system permits either tape or source monitoring and echo recording
- Mechanical automatic shut off and easy tape loading mechanism
- Tape selector switch and recording bias control
- Sound on sound system
- 4-digit tape counter
- Playback volume



TOSHIBA



# 4 CHANNEL STEREO TAPE DECK PT-866

## SPECIFICATIONS

### GENERAL

- Power source:** AC 100/110/120/200/220/240 V, 50 or 60 Hz
- Usable tape:** Open reel tape, up to 7"
- Tape speed:** 19(7½), 9.5(3¾), 4.8(1⅞) cm/sec. (ips)
- Track & channel:** 4-track 2-channel stereo record & playback, 4-channel playback
- Bias & erasure:** AC, 85 kHz
- Input jack:** Microphone, Line-input, DIN
- Output jack:** 4-Line output, Headphone, DIN
- Motor:** 4-pole condenser motor
- Controls:** Tape selector switch, speed change, power switch, volume control, mode selector
- Operations:** Rotary (PLAY, STOP, F.F., REW.), PAUSE
- Auxiliary device:** 4-digit tape counter, easy loading mechanism, recording bias control
- Dimensions:** 400(W) x 440(H) x 222(D) mm (15" x 16¼" x 8¾")
- Weight:** 15 kg (33 lbs.)
- Accessory:** 7" blank reel, AC cord, head cleaning stick, PIN type patch cord, owner's manual



### PERFORMANCE

- Output level & impedance:** 0–1 V (Variable), 500Ω (DIN; 0.5 V 6.8 kΩ)
- Frequency response:** 50–20,000 Hz
- Tape speed tolerance:** ±1%
- Wow & flutter:** 0.09% w.r.m.s.
- Cross talk:** 60 dB
- Channel separation:** 55 dB
- Signal-to-Noise ratio:** 56 dB
- Erasure:** 65 dB
- Input level & impedance:** MIC; –65 dB 10 kΩ, Line-in; –23 dB 820 kΩ
- FF time:** 180 sec. (7" 100% tape)
- Rewind time:** 180 sec. (7" 100% tape)