



# TOSHIBA STEREO TAPE DECK

## SERVICE DATA MODEL PT-884

FILE NO. 100-071



### SPECIFICATIONS

Usable Tape:	3", 5", 7"	Signal/Noise Ratio:	56 db minimum
Tape Speed:	7-1/2", 3-3/4" and 1-7/8ips(3 speeds)	Wow/Flutter:	0.09% R.M.S. maximum at 7-1/2ips
Track:	4 track 4 channel Stereo and 4 track 2 channel		0.12% R.M.S. maximum at 3-3/4ips
Recording System:	AC bias at 105 KHz		0.18% R.M.S. maximum at 1-7/8ips
Erasing System:	AC erase	Power Consumption:	60 watts maximum (VK, TE) 50 watts maximum (TA)
Frequency Response:	20 to 25000 Hz at 7-1/2ips 30 to 15000 Hz at 3-3/4ips 30 to 9000 Hz at 1-7/8ips	Semi-Conductor:	8 ICS, 24 transistors 26 Diodes
Power Output:	LINE OUT 0 to 1volt	Head:	3 heads
Input Jack:	MIC. -65db LINE IN. -23db	Dimensions:	(W) 15-13/16" (H) 17-3/8" (D) 8-3/4"
Output Jack:	LINE OUT HEADPHONE (4 channel)	Weight:	30 lbs
Power Source:	AC 100/120/220/240 volts, 50/60 Hz		

TOKYO SHIBAURA ELECTRIC CO., LTD.

2-1, 5-CHOME, GINZA CHIU-KU TOKYO, JAPAN