

# STEREO RECORD PLAYER SR-300C

- High compliance induced magnet type cartridge
- Quiet 4-pole hysteresis synchronous motor
- Perfect double-floating advanced belt-driven system
- Cueing control and auto-return/auto-cut player



# STEREO RECORD PLAYER **SR-300C**

## SPECIFICATIONS

<b>Cartridge:</b>	Induced magnet, type C-27M
<b>Turn table:</b>	30 cm (12"), aluminum diecast, belt-driven
<b>Tone arm:</b>	S-shaped pipe arm with EIA standard cartridge socket
<b>Tracking error:</b>	$\pm 1.5^\circ$
<b>Motor:</b>	4-pole hysteresis synchronous motor
<b>Speed:</b>	33 $\frac{1}{3}$ , 45 (r.p.m.) mechanical change-over
<b>Wow &amp; flutter:</b>	0.1% (w.r.m.s.) or less
<b>Stylus:</b>	0.7 (mil) round, corundum, type N-13C (Ultra C)
<b>Output:</b>	6 mV (5 cm/sec., 1 kHz)
<b>Output balance:</b>	$\pm 3$ dB or less
<b>Compliance:</b>	$20 \times 10^{-3}$ cm/dyne (DC), $6 \times 10^{-6}$ cm/dyne (100 Hz)
<b>Optimal stylus pressure:</b>	3 g
<b>Frequency response:</b>	20–18,000 Hz
<b>Cross talk:</b>	15dB (1 kHz) or better
<b>Signal-to-Noise ratio:</b>	45dB or better
<b>Auxiliary device:</b>	Auto-cut, auto-return, arm-elevation
<b>Accessory:</b>	Owner's manual, stylus pressure gauge, 45 r.p.m. adaptor, spare pulley, screw driver, shell weight (3 g), oil
<b>Cabinet:</b>	Walnut finish, smoked acril resin cover
<b>Power source:</b>	AC 115/230 V, 50 or 60 Hz
<b>Dimensions:</b>	450(W) $\times$ 180(H) 350(D) mm (17 $\frac{1}{8}$ " $\times$ 7 $\frac{1}{16}$ " $\times$ 13 $\frac{3}{4}$ " )
<b>Weight:</b>	6.5 kg (14 $\frac{5}{16}$ lbs.)



© beim Hersteller  
Archiv Michael Otto  
HiFi-Classic.de