

CONCAVE SPEAKER SYSTEM

SS-17/24/22

- SS-17 • 2-way speaker system of 30W power handling capacity • Handsome walnut cabinet with removable grill panel.
- SS-24 • 2-way speaker system • Large 30W power handling capacity • Walnut finished cabinet.
- SS-22 • 20W power handling capacity • Beautiful walnut finished cabinet.



SS-22

SS-24

SS-17

CONCAVE SPEAKER SYSTEM **SS-17/24/22**

SPECIFICATIONS

SS-17

Enclosure: Infinit baffle type
Mounted speakers: Woofer; 20 cm (8"), concave
 Tweeter; 7 cm (3"), cone
Frequency range: 50–20,000 Hz
Cross-over frequency: 6,000 Hz
Power handling capacity: 30 W (Max.)
Impedance: 8Ω
Sensitivity: 93 dB/IEC
Fundamental resonance frequency: 95 Hz
Front panel: Removable
Dimensions: 270(W) × 440(H) × 220(D) mm
 (10⁵/₈" × 17⁵/₁₆" × 8¹/₁₆")
Weight: 5 kg (11 lbs.)

SS-24

Enclosure: Infinit baffle type
Mounted speaker: Woofer; 20 cm (8"), concave
 Tweeter; 7 cm (3"), cone
Frequency response: 50–20,000 Hz
Cross-over frequency: 6,000 Hz
Power handling capacity: 30 W (Max.)
Impedance: 8Ω
Sensitivity: 93 dB/IEC
Fundamental resonance frequency: 95 Hz
Front panel: Fixed
Dimensions: 308(W) × 439(H) × 193(D) mm
 (12¹/₈" × 17¹/₄" × 7⁵/₈")
Weight: 4.5 kg. (10 lbs.)

SS-22

Enclosure: Infinit baffle type
Mounted speakers: 16 cm (6¹/₂"), full range
Frequency range: 80–12,000 Hz
Power handling capacity: 20 W (Max.)
Impedance: 8Ω
Sensitivity: 92 dB/IEC
Fundamental resonance frequency: 130 Hz
Front panel: Fixed
Dimensions: 221(W) × 375(H) × 166(D) mm
 (8³/₄" × 14³/₄" × 6¹/₂")
Weight: 2.7 kg (6 lbs.)

FREQUENCY RESPONSE

